Transshipment Crane Barge 6324

HARVEST DANUBE



GENERAL Reference Delivery date Basic functions

Classification

Descriptive note

Flag (at delivery)

DIMENSIONS

Length moulded Beam moulded Depth at sides Draught scantling Draught design Deadweight max. Working deck

TANK CAPACITIES

Fuel oil Fresh water Sewage & Grey water Lub. oil Dirty oil / Sludge Bildge water Water ballast

CRANE PERFORMANCE

 Make and type
 Liebherr

 Operation
 Prepared

 SWL sheltered water
 45 ton @

 SWL open sea operation
 35 ton @

 Hoisting speed (35 T)
 0-60 m/r

 Hoisting speed (45 T)
 0-46 m/r

 Luffing time 12-36 M
 63 sec.

 Simultaneous speed with 3 Slewing ar

 (after acceleration)

 Optimized high
 1 x 38.0

 Performance grabs
 1 x 29.5

December 2017 Transshipment of bulk cargoes from river barges to bulk vessels Lloyd's Register of Shipping: * 100 AT, Pontoon, *IWS Crane Pontoon, manned working up to 20 nm offshore, unmanned towing St. Vincent and the Grenadines

63,00 m 23.50 m 4,50 m 3,50 m 2.50 m 1,905 ton (excl. grabs) 880 m2 (10 ton/m²)

238 m3 87 m3 80 m3 5 m3 10 m3 5 m3 1.756 m3

522006

Liebherr CBG 350 Prepared for Grab, Containers or hook 45 ton @ 12-36 m (excl. attachments) 35 ton @ 12-36 m (excl. attachments) 0-60 m/min 0-46 m/min 63 sec. Full load and speedmotions Slewing and Luffing at full load and motions sp

 Luffing time 12-36 M
 63 sec.

 Simultaneous speed with 2 Full load and speedmotions

 Simultaneous speed with 3 Slewing and Luffing at full load and motions speed, hoisting 60% (after acceleration)

 Optimized high
 1 x 38.0 m3

 Performance grabs
 1 x 29.5 m3

1 x ∠9.5 m3 1 x 12.5 m3

AUXILIARY EQUIPMENT

Main generator set Back-up generator Power each 440 V, 60 Hz Harbor generator set Power

DECK LAY-OUT

Anchor mooring system Anchors Towing brackets JIB rest Deck covering Container fittings Fender system Life rafts Workboat Boat landing

2 x Caterpillar C18 1 x Caterpillar C18 545 kVA / 436 ekW (1800 rpm),

1 x Caterpillar C4.4 95 kVA / 76 ekW (1800 rpm), 440 V, 60 Hz

4 DMT Electric double drum winches 3 Anchors 3 Towing brackets Slim design, with positioning system 440 m2 fir wood For 28 TEU or 14 FEU locations or a combination With a stack load of 50 ton 1/3 steel pipe fenders, Tyre fenders 2 inflatable liferafts for 6 persons Dinghy with davit on aft deck

For easy access to the barge on the aft and front of the barge aboat landing with stairs are provided

ACCOMMODATION

Day accommodation with pantry, change room and office for a maximum of 12 persons, provided with ventilation, air conditioning and heating.

NAUTICAL AND COMMUNICATION EQUIPMENT

Navigation lighting and communication system according Classification





Transshipment Crane Barge 6324



